



-- Search JLG --

Change Region Language English

Telehandlers » SkyTrak » 10054

10054 Specifications

General

Rated Capacity @ 24" Load Center	10,000 lb / 4,536 kg
Maximum Lift Height	53' 2" / 16.21 m
Capacity @ Maximum Lift Height	*4,000 lb / *1,814 kg
Maximum Reach	*26'/**39' / *7.92 m/**11.89 m
Capacity @ Maximum Reach	3,000 lb / 1,361 kg
Approximate Operating Weight	27,323 lb / 12,394 kg
Length (Less Forks)	238.8" / 6.07 m
Width	102" / 2.59 m
Height	101.1" / 2.57 m
Wheelbase	119.5" / 3.04 m
Outside Turning Radius	164" / 4.17 m
Ground Clearance	18" / 45.7 cm
Drive	4 x 4
Engine	Cummins QSB4.5T
HP @ RPM	110 hp @ 2,500 rpm
Transmission	Powershift
Axle-Front	High-Bias, Limited Slip
Axle-Rear	Planetary
Steering	All-Wheel
Tires	17.50 x 25-12 Ply
Maximum Travel Speed	20 mph / 32 kmph
Frame Tilt Left/Right	±10 Degrees

*With outriggers down.

[Specifications](#)
[Comparison](#)
[Attachments](#)

Downloads

- [Product Brochure](#)
- [Specification Sheet](#)



[Print](#)

[Home](#)

[Products](#)

[Aerial Work Platforms](#)

[Telehandlers](#)

[Stock Pickers](#)

[Drop-deck Trailers](#)

[Military & Government](#)

[Personal Portable Lifts](#)

[Used Equipment](#)

[Industries](#)

[Financial Solutions](#)

[Services](#)

[Government/Military](#)

[Career Center](#)

[Safety](#)

[About JLG](#)

[Distributor Locator](#)

[My JLG](#)

[Contact Us](#)